

TECHNICAL SPECIFICATION SHEET

Machine Particulars	Value
MODEL	
CENTER HEIGHT	205
SWING OVER CROSS SLIDE	255
WIDTH OF BED	250 MM
ADMITS BETWEEN CENTER	1000 MM
SPINDLE BORE	52 mm
SPINDLE NOSE	D1-6
TAPER OF SPONDLE NOSE	MT-6
SPINDLE SPEED	16/ 45-1800 RPM
COMPOUND REST TRAVEL	140 MM
CROSS SLIDE TRAVEL	210 MM
LEAD SCREW THREADS	4 TPI
LONGITUDINAL FEEDS	0.05—1.7 mm/rev.
CROSS FEEDS	0.025—0.85 mm/rev.
TOOL SHANK SIZE	20*20 mm
METRIC THREAD	39/0.2-14 MM
TAIL STOCK QUIL DIAMETER	50 mm
TAIL STOCK QUILL TAPER	MT-4
MAIN MOTOR POWER	3 HP 440 VOLT
COOLANT PUMP	YES
ADDITIONAL OPTIONAL ACCESSORIES AVAILABLE	4 JAW INDEPENDENT CHUCK 3 JAW SELF CENTERING CHUCK 2 – AXIS DRO TAPER TURNING ATTACHMENT TOOL POST GRINDER